

“जल का साथी
आपके
कल का साथी”
SNT पम्पस



**OPENWELL
SUBMERSIBLE
PUMPS**



SNT[®]
ELEC
INNOVATION IN QUALITY
(An ISO 9001 : 2015 Certified Company)

Special Feature

- Special Hi flow & Hi head Models
- Long durability due to non-corrosive SS.body
- Low Power Consumptions
- Excellent Performance in Low Voltage



Operating Limits

- Power Range Single Phase - 240v
- 3 Phase - 420v
- Frequency - 50Hz AC
- Speed - 2800 RPM
- Max. Temp -30°C



V-7 Horizontal Openwell Submersible Pumps

S.NO	HP	Pipe Size	Rotor	Phase	TOTAL HEAD IN METERS					
					10	14	18	22	26	28
					DISCHARGE IN LPM					
1	0.50	25x25	AR	SP	120	90	45	20		
2	1.00	32x25	AR	SP	200	175	135	125	100	
3	1.50	32x32	AR	SP	400	350	290	220	180	80
4	2.00	50x50	AR/CR	SP/TP	510	460	360	320	200	120
5	3.00	65x50	AR/CR	SP/TP	600	515	385	340	220	140
6	5.00	65x65	AR/CR	TP	745	600	510	450	290	200

V-9 Horizontal Openwell Submersible Pumps

S.NO	HP	Pipe Size	Rotor	Phase	TOTAL HEAD IN METERS								
					10	14	18	22	26	28	32	36	38
					DISCHARGE IN LPM								
1	3.00	65x65	AR/CR	SP/TP	890	760	610	400	180				
2	3.00	65x50	AR/CR	SP/TP			640	560	500	450	200		
3	5.00	65x65	CR	SP/TP	1020	980	870	700	530	390	160		
4	5.00	65x50	CR	SP/TP			680	620	530	510	400	240	
5	7.50	65x65	CR	TP	1150	1075	1035	980	930	870	660	315	250

AR - Alluminium Rotor | SP - Single Phase | LPM - Liter Per Minutes | CR - Copper Rotor | TP - Three Phase



SNT Sales Pvt. Ltd.

📍 Jaipur (Rajasthan) India

✉️ sntsalespvtltd@gmail.com

🌐 Web - www.sntsales.in

